

ACCUMETRIC

JOBGING ITEM NO.	SIZE	COLOR	PK
9705-001	310CL	Cartg. Clear	12
9705-002	310WH	Cartg. White	12

ALABAMA MACHINERY

JOBGING ITEM NO.	SIZE	PK
9930-303	80052 1/2" x 800' spool	1
9930-304	80053 3/4" x 400' spool	1

DAP

JOBGING ITEM NO.	SIZE	COLOR	PK
9785-074	08642	Cartg. Black	12
9785-075	08643	Cartg. Aluminum	12
9785-076	08647	Cartg. Bronze	12

JOBGING ITEM NO.	SIZE	COLOR	PK
9825-002	18001 5.5 oz.	White	12

JOBGING ITEM NO.	SIZE	COLOR	PK
9981-279	18152	Cartg. White	12
9981-280	18156	Cartg. Clear	12
9981-281	18130	Cartg. Almond	12

JOBGING ITEM NO.	SIZE	COLOR	PK
9981-286	18826	12 oz. White	12

BOSS® 310 INDUSTRIAL SEALANT

- A one-part acetoxycure adhesive/sealant suitable for general industrial uses
- Adheres to clean metal, glass, many types of wood, RTV silicones, vulcanized silicone rubber and ceramics
- Resists weathering, vibration, moisture and extremes in temperature

Meets NSF Standard 51



BACKER ROD ETHAFOAM SB SEALANT

Commonly used in glazing installations, window and door applications, expansion joints, curtain wall joints, partitions, log construction, pavement joints, repairs, precast units and copings. It is inserted into a joint to control sealant depth to create a backstop to: Allow proper sealant tooling. Allow proper sealant wetting of the joint surfaces. Insulate underside of sealant. Yield proper bond breaker between the Backer Rod and sealant.



It can also be used as a temporary joint seal.

DAP® 100% SILICONE RUBBER SEALANT 10.1 OZ.

- All purpose, indoor/outdoor use
- Watertight seal
- Long-lasting flexibility
- Minimal shrinkage
- 50 year durability guarantee

Meets TT-S-001543A, Class A



DAP® KWIK SEAL® Tub & Tile Adhesive Caulk

- Bonds like a glue and seals like a caulk.
- Provides a durable, watertight seal.
- Excellent adhesion and flexibility. Tools easily.
- Cured caulk is mildew resistant.
- Paintable. Easy water clean-up.



DAP® ALEX PLUS® Acrylic Latex Caulk Plus Silicone 10.1 OZ.

- Provides Durable, Flexible Seal
- Cured Caulk is Mildew Resistant
- Interior/Exterior Use
- Paintable. Water clean-up.

Exceeds ASTM Spec C834



DAP® DAPtex® Multi-Purpose Latex Insulating Foam Sealant

- Seals gaps and saves energy
- Won't over expand
- Interior/Exterior Use - Non-clogging applicator
- Paintable, toolable. Water clean-up.



MOBILE PAINTS

JOBGING ITEM NO	SIZE	COLOR	PK
60-11-43	Cartg.	Bronze	12
60-12-43	Cartg.	Brown	12
60-15-43	Cartg.	Cedar	12
60-18-43	Cartg.	Gray	12
60-21-43	Cartg.	White	12
60-22-43	Cartg.	Almond	12

JOBGING ITEM NO	SIZE	COLOR	PK
60-23-43	Cartg.	Clear	12

JOBGING ITEM NO	SIZE	COLOR	PK
60-17-43	Cartg.	White	12

**Volume
Pricing**
on
Full Pallet = 1440
1/2 Pallet = 720
1/4 pallet = 360

WEATHERTITE™**PREMIUM 100****ACRYLIC ADHESIVE**

A quality 100% Acrylic Caulk fortified with silicone to help increase adhesion for hard to adhere to substrates like aluminum and glass. This caulk meets the requirements of ASTM C-834. 10.1 fl. oz. Cartridge

**PREMIUM 100 - CLEAR
WATERBORNE ACRYLIC PAINTABLE****WEATHERTITE™ 101 PLUS
SILICONIZED ACRYLIC WHITE**

A quality 100% Acrylic Sealant with silicone is designed for slower curing to allow for easier tooling. This brilliant white caulk meets the requirements of ASTM C-834 Type OP, Grade -18° C. 10.1 fl. oz. Cartridge



JOBGING DESCRIPTION	PK
60-07 180 PIECE CAULK DISPLAY	1

DISPLAY CONTENTS:

JOBGING	COLOR	PK
60-21-43	White	60
60-11-43	Bronze	12
60-12-43	Brown	12
60-15-43	Cedar	6
60-18-43	Gray	12
60-22-43	Almond	18
60-17-43	White 101 Plus	60

SIDE RACK
24" DISPLAY RACK
HEADER FOR DISPLAY

**WEATHERTITE™
CAULK DISPLAY**

251-443-6110
251-408-0410 Fax

Toll Free: 1-800-621-6952
(In Alabama) 1-800-672-6707



RED DEVIL, INC.

JOBGING ITEM NO **PK**
9952-021 4071 6

JOBGING ITEM NO **PK**
9952-022 4070 6

JOBGING ITEM NO **SIZE** **PK**
9952-023 0409 10.1 fl. oz. 12

JOBGING ITEM NO **SIZE** **PK**
9952-024 4072 Bag of 25 1

Create-A-Color® PRO CAULK MIXER

Constructed of die cast aluminum, this unique product tints a single tube of Create-A-Color® Caulk with ordinary latex paint. Portable and convenient, it is simple to use and cleans easily with soap and water. Includes syringe for extracting paint and easy-to-follow instruction guide.

Create-A-Color® STANDARD CAULK MIXER

Constructed of sturdy plastic, this unique product tints a single tube of Create-A-Color® Caulk with ordinary latex paint. Portable and convenient, it is simple to use and cleans easily with soap and water. Includes syringe for extracting paint and easy-to-follow instruction guide.

Create-A-Color® CAULK

Specially formulated to be tinted using a Red Devil Create-A-Color® Caulk Mixer, this superior quality sealant offers excellent adhesion to most surfaces. It provides a long-lasting, mildew-resistant seal that cures to an ultra-smooth, satin finish. Interior/exterior. Odorless. Water clean up.

PACK of 25 SYRINGES FOR Create-A-Color® CAULK SYSTEM

Pack of 25 additional syringes for use with the Red Devil Create-A-Color® system



TOWER SEALANT

JOBGING ITEM NO **SIZE** **COLOR** **PK**
9751-002 TS-00293 Cartg. White 12
9751-001 TS-00295 Cartg. Clear 12

JOBGING **DESCRIPTION** **PK**
9751-100 Assortment 1

Assortment Includes:

24 ea. White 24 ea. Clear 12 each 7 Colors

JOBGING ITEM NO **SIZE** **COLOR** **PK**
9751-101 TS-00215 Cartg. White 24
9751-102 TS-00142 Cartg. Off White 12
9751-103 TS-00147 Cartg. Limestone 12
9751-104 TS-00194 Cartg. Tan 12
9751-105 TS-00196 Cartg. Stone 12
9751-106 TS-00220 Cartg. Aluminum Gray 12
9751-107 TS-00225 Cartg. Redwood Tan 12
9751-108 TS-00123 Cartg. Bronze 12
9751-109 TS-00130 Cartg. Clear 24

TOWER SILICONE ALL PURPOSE 100% SILICONE

Is a general purpose silicone sealant, forms a permanent water-proof flexible seal and has excellent primer-less adhesion to most common materials. Meets the FDA regulations for incidental food contact and can be used for kitchen and sanitary applications. Use interior or exterior on glass, tiles, ceramic tile, painted wood, plastic and more.

TOWER TECH² ACRYLIC URETHANE ELASTOMERIC SEALANT

Exceeds ASTM C-920
TowerTech² has superior adhesion and with 800% elongation it forms a flexible, durable airtight, water resistant seal offering exceptional protection from extreme weather conditions. Once cured, the bead is mildew resistant and exceeds the requirements of Fed. Spec. TTS-00230C, Type S, Class A; ASTM C-920, Grade NS, Class 25 and ASTM C-834 Type OP, Grad-18°C



251-443-6110

251-408-0410 Fax

Toll Free:

(In Alabama)

1-800-621-6952

1-800-672-6707

